## APPENDIX 12: IMO SHIP/SHORE SAFETY CHECKLIST APM TERMINALS PIPAVAV

For Loading or Unloading Dry Bulk Cargo Carriers				
Date				
Port Loading				
Terminal/Quay				
Available depth of water in berth				
Minimum air draught*				
Ship's name				
Arrival draught (read/calculated)				
Air draught				
Calculated departure draught				
At the state				
Air draught				

The Master is responsible at all times for the safe loading and unloading of the ship, details of which should be confirmed to the terminal in the form of loading or unloading plan (see example loading/unloading plans on back cover). In addition the Master should ensure that the checklist is completed in consultation with the terminal before loading or unloading is commenced.

The Master and terminal manager, or their representatives, should complete the checklist jointly. Advice on points to be considered is given in the accompanying guidelines. The safety of operations requires that all questions should be answered affirmatively and the boxes ticked. If this is not possible, the reason should be given, and agreement reached upon precautions to be taken between ship and terminal. If a question is considered to be not applicable write 'N/A', explaining why if appropriate.

1. Is the depth of water at the berth, and the air draught, adequate for the cargo operations?  The term air draught should be construed carefully if the ship is in a river or an estuary, it usually refers to maximum mast height for passing under bridges, while on the berth it usually refers to the height available or required under loader or unloaders.  2. Are mooring arrangements adequate for all local effects of tide, current, weather, traffic and craft alongside?  3. In emergency, is the ship able to leave the berth at any time?  4. Is there safe access between the ship and the wharf? Tended by Ship/Terminal (cross out the appropriate)  5. Is the agreed ship/terminal communications system operative? Communication method  Language  Radio channels/phone numbers	Terminal
a river or an estuary, it usually refers to maximum mast height for passing under bridges, while on the berth it usually refers to the height available or required under loader or unloaders.  2. Are mooring arrangements adequate for all local effects of tide, current, weather, traffic and craft alongside?  3. In emergency, is the ship able to leave the berth at any time?  4. Is there safe access between the ship and the wharf? Tended by Ship/Terminal (cross out the appropriate)  5. Is the agreed ship/terminal communications system operative?  Communication method  Language	
current, weather, traffic and craft alongside?  3. In emergency, is the ship able to leave the berth at any time?  4. Is there safe access between the ship and the wharf? Tended by Ship/Terminal (cross out the appropriate)  5. Is the agreed ship/terminal communications system operative?  Communication method  Language	
4. Is there safe access between the ship and the wharf? Tended by Ship/Terminal (cross out the appropriate)  5. Is the agreed ship/terminal communications system operative?  Communication method  Language	
Tended by Ship/Terminal (cross out the appropriate)  5. Is the agreed ship/terminal communications system operative?  Communication method  Language	
Communication method  Language	
Radio channels/phone numbers	
6. Are the liaison contact persons during operations positively identified?	
Ship contact persons	
Shore contact person(s)	
Location	
7. Are adequate crew on board and adequate staff in the terminal, for emergency?	
8. Have any bunkering operations been advised and agreed?	
9. Have any intended repair to wharf or ship whilst alongside been advised and agreed?	
10. Has a procedure for reporting and recording damage from cargo operations been agreed?	

S.No.		Ship	Terminal
11.	Has the ship been provided with copies of port and terminal regulations, including safety and pollution requirements and		
	details of emergency services?		
12.	Has the shipper provided the Master with the properties of the cargo in accordance with the requirements of Chapter VI of		
	SOLAS?		
13.	Is the atmosphere safe in holds and enclosed spaces to which access may be required have fumigated cargoes been identified,		
	and has the need for monitoring of atmosphere been agreed by ship and terminal?		
14.	Have the cargo handling capacity and any limits of travel for each loader/ unloader been passed to the ship/terminal?		
	Loader No. Rate Tonnes/hr		
	Loader No. Rate Tonnes/hr		
	Loader No. Rate Tonnes/hr		
15.	Has a loading/unloading been calculated for all stages of loading/deballasting or unloading/ballasting?		
	Copy lodged with		
16.	Has the holds to be worked been identified in the loading or		
	unloading plan, showing the sequence of work, and the grade and tonnage of cargo to be transferred each time the hold is worked?		
17.	Has the need for trimming of cargo in the holds been discussed and the method and extent been agreed?		
18.	Does both ship and terminal understand and accept that if the ballast programme becomes out of step with the cargo operation,		
	it will be necessary to suspend cargo operation until the ballast		
19.	operation has caught up?  Have the intended procedures for removing cargo residues lodged		
10.	in the holds while unloading, been explained to the ship and accepted?		
20.	Have the procedures to adjust the final time of the loading ship been decided and agreed?		
	Tonnage held by the terminal conveyor system.		

S.No.		Ship	Terminal
21.	Has the terminal been advised of the time required for the ship to		
	prepare for sea, on completion of cargo work?		

## THE ABOVE HAS BEEN AGREED:

Time	Date	
For Ship	For Terminal	
Rank	Position/Title	